

**Project:**  
**Reference Number:**
**Client:**  
**Client Number:**  
**Contact:**

Qty.	Description
1	<p data-bbox="199 436 446 470"><b>UNILIFT KP.350.AV.1</b></p>  <p data-bbox="590 784 1061 806" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="199 817 502 873">Product No.: <a href="#">013N7900</a> Submersible drainage pump</p> <p data-bbox="199 907 718 1052">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.</p> <p data-bbox="199 1086 670 1176">The pump is fitted with a suction strainer, a carrying handle and is supplied with a 10 m mains cable.</p> <p data-bbox="199 1209 718 1288">The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p data-bbox="199 1321 710 1377">The pump has a double shaft seal consisting of two lip seals with grease in-between.</p> <p data-bbox="199 1411 758 1534">The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid</p> <p data-bbox="199 1568 710 1590">The motor is filled with a non-toxic motor liquid.</p> <p data-bbox="199 1624 694 1713">Liquid: Liquid temperature range: 0 .. 40 °C Density: 998.2 kg/m<sup>3</sup></p> <p data-bbox="199 1747 1364 1870">Technical: Maximum flow: 3.89 l/s Max. Particle: 10 mm Approvals: CE,RCM,VDE,LGABG,EAC,TUVRHWID,MORO,UKCA,CHROHS,SEPRO</p> <p data-bbox="199 1904 726 2105">Materials: Pump housing: Stainless steel EN 1.4301 AISI 304 Impeller: Stainless steel EN 1.4301 AISI 304</p>



**Company name:** national pumps and boilers  
**Created by:**  
**Phone:** 01539 729395  
**Email:** info@nationlapumpsandboilers.co.uk  
**Date:** 03/01/2024

**Project:**  
**Reference Number:**

**Client:**  
**Client Number:**  
**Contact:**

Qty.	Description
1	<p>Installation:</p> <p>Range of ambient temperature: 0 .. 50 °C</p> <p>Type of connection: Rp</p> <p>Size of connection: 1 1/4 inch</p> <p>Maximum installation depth: 7 m</p> <p>Place of installation: Indoor/outdoor</p> <p>Electrical data:</p> <p>Power input - P1: 720 W</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 220-240 V</p> <p>Rated current: 3.2 A</p> <p>Capacitor size - run: 10 µF/400 V</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): F</p> <p>Length of power cable: 10 m</p> <p>Type of cable plug: NONE</p> <p>Others:</p> <p>Net weight: 8 kg</p> <p>Gross weight: 8.3 kg</p> <p>Shipping volume: 0.013 m<sup>3</sup></p> <p>Environmental approvals: WEEE</p>

**Project:**  
**Reference Number:**

**Client:**  
**Client Number:**  
**Contact:**

Description	Value
<b>General information:</b>	
Product name:	UNILIFT KP.350.AV.1
Product No:	013N7900
EAN number:	5700393781665
<b>Technical:</b>	
Maximum flow:	3.89 l/s
Maximum head:	9 m
Max. Particle:	10 mm
Approvals:	CE,RCM,VDE,LGABG,EAC,TUV RHWID,MORO,UKCA,CHROHS, SEPRO
Model:	A
<b>Materials:</b>	
Pump housing:	Stainless steel
Pump housing:	EN 1.4301
Pump housing:	AISI 304
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI 304
<b>Installation:</b>	
Range of ambient temperature:	0 .. 50 °C
Type of connection:	Rp
Size of connection:	1 1/4 inch
Maximum installation depth:	7 m
Place of installation:	Indoor/outdoor
<b>Liquid:</b>	
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Power input - P1:	720 W
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	3.2 A
Capacitor size - run:	10 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	CONTACT
Thermal protec:	INT.
Length of power cable:	10 m
Type of cable plug:	NONE
<b>Controls:</b>	
Level switch:	AV
<b>Others:</b>	
Net weight:	8 kg
Gross weight:	8.3 kg
Shipping volume:	0.013 m <sup>3</sup>
Environmental approvals:	WEEE

