

Data sheet

Hydraulic data

Maximum operating pressure P_N	10 bar
Head max H_{max}	0.0 m
Flow max Q_{max}	41.0 m ³ /h
Minimum suction head at 50 °C m	5 m
Minimum suction head at 95 °C m	9 m
Minimum suction head at 110 °C	23 m
Min. fluid temperature T_{min}	-10 °C
Max. fluid temperature T_{max}	110 °C
Min. ambient temperature T_{min}	-10 °C
Max. ambient temperature T_{max}	40 °C

Motor data

Energy efficiency index (EEI)	0.17
Mains connection	1~230 V ±10%, 50/60 Hz
Min current I_{min}	0.2 A
Max current I_{max}	2.47 A
Rated power P_2	470 W
Min. speed n_{min}	650 1/min
Max. speed n_{max}	3200 1/min
Power consumption $P_{1 min}$	10 W
Power consumption $P_{1 max}$	560 W
Interference emission	EN 61800-3;2004+A1;2012 /residential area (C1)
Interference immunity	EN 61800-3;2004+A1;2012 /industrial environment (C2)
Insulation class	F
Protection class	IPX4D
Threaded cable connection	5 x M16x1.5

Installation dimensions

Pipe connection on the suction side DN_s	DN 65
Pipe connection on the discharge side DN_d	DN 65
Port-to-port length L_0	280 mm

Materials

Pump housing	Grey cast iron
Impeller	PPS-GF40
Shaft	1.4028, DLC-coated
Bearing	Carbon, antimony-impregnated

Dimensions and dimensions drawings

Stratos MAXO 65/0,5-9 PN6/10

