GRUNDFOS X Project: Reference Number:		Company name: Created by: Phone: Email: Date: Client: Client: Client Number:	national pumps and boilers 01539 729395 info@nationlapumpsandboilers.co.uk 02/01/2024	
		Contact:		
Qty.				
1	MI 301			
		Product picture may differ from actual p	roduct	
	<ul> <li>Product No.: 98046408</li> <li>The Grundfos GO Remote is used to establish wireless connection to a Grundfos product, using a standard Android or iOS platform, with the Grundfos GO Remote App installed. The App is available from Apple App Store and Google Play free of charge.</li> <li>The MI 301 is a module with built-in infrared and radio communication. It must be used in conjunction with an Android or iOS-based Smartphone with Bluetooth Low Energy connection. The MI 301 module has rechargeable Li-ion battery and must be charged separately.</li> <li>The pump/system can be monitoried and controlled from the Grundfos GO, and it will be possible to create pdf reports. The specific functions available depend on each individual product.</li> </ul>			
		os MI 301 charger uide		

Company name: Created by: Phone: Email: Date:	national pumps and boilers 01539 729395 info@nationlapumpsandboilers.co.uk 02/01/2024	
Client: Client Number: Contact:		

## Project: Reference Number:

Description	Value
General information:	
Product name:	MI 301
Product No:	98046408
EAN number:	5710628055591
Installation:	
Range of ambient temperature:	-20 70 °C
Relative humidity:	95 %
Operating temp.:	-10 °C
Operating temp.:	50 °C
Electrical data:	
Voltage supply:	Li-ion battery 3.7 V, 560 mAh, 2.1 Wh
Maximum current consumption:	0.03 A
Enclosure class (IEC 34-5):	IP40
Others:	
Danish VVS No.:	380679301
Swedish RSK No.:	5731821
Finnish LVI No.:	4615956
Norwegian NRF no.:	9040866
Country of origin:	ТН
Custom tariff no.:	85371098

